


DATI TECNICI - TECHNICAL DATA	
SCALA RANGE:	0/90°C
DIFFERENZIALE / DIFFERENTIAL :	4 ± 2,5°C
TOLL. VALORI F.S.	± 3°C
CAPILLARE / CAPILLARY :	MM 1500 RAME / COPPER OR INOX CAPILLARY
INVOLUCRO MANOPOLA / CASE:	LIGHT BLUE PANTONE 2995C
SERIGRAFIA / DIAL :	RED KNOB - WHITE NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY :	C1 15(2,5)A 400 VAC - C2 2,5(0,4)A 400 VAC
MINIMUM CORRENT :	200 mA
INSULATION RESISTANCE :	>100 M ohm
TEST DI VITA / LIFE OF PRODUCT :	100.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE	80°C
GRADO TENUTA / IP GRADE	IP 40



MODIFICA		DOC.RIF.	DATA	APPARECCHIO ASSIEME PARTICOLARE ARTH097	
1					
2				MATERIALE	
3				TRATTAMENTO	
4					
5				NOTE	
					DISEGNATO A. SALA APPROVATO SALA A. SCALA 1 : 1 DATA 11/11/2011 CODICE ARTH097