



PDKA22BB10

Carton Box pieces	Qty	1
Product	Foot Switch	
Model	with Hole for Metal Bar	
Feature	Double	
Contact	(1NO+1NC)+(1NO+1NC)	
Color	Yellow	
Protection	Metal Protection	
Current	Ie	3 A (240V AC)
Usage Category	AC15	
Mechanical Life	Min Qty	1000000
Electrical Life	Min Qty	100000
Operating Frequency	On-Off/Hour	Mech. 1800 Elec. 1200
Insulation Voltage	Ui	300 V
Impulse Withstand Voltage	Uimp	2.5 kV
Dielectric Strength (Body-Contact)	2.500V AC	
Dielectric Strength (Contact-Contact)	1.500V AC	
Isolation Resistance	10 MΩ min. (500V DC)	
Operating Temperature	-25 / +80 °C	
Pollution Degree	3	
Protection Degree	IP65	
Contact Material	AgNi	
Cable Section	1.5-2.5 mm ²	
Screw Torque	1.5Nm	
Short Circuit Breaking Capacity	Ics	1 kA
Body Material	Plastic	
Production Time	31.12.1899 00:00:00	
Serial	PDK Series	
Specifications	Plastic or Metal options	

	Single and Double Speed
	Yellow
	Grey and orange color options
	with Latching option
	TS EN 60947-5-1 UL 508 VDE 0660
Standards / Certificates	   

PDKA22BB10

