

## Outline drawing

Power supply voltage	Applicable standard motor (kW)	Inverter model	Outside dimensions (mm)					Mounting dimensions (mm)					
			View	W	H	D	D1	D2	View	W1	W2	H1	H2
3-phase 400V	0.75	FRN0.75AQ1□-4E	A	150	465	262	162	100	B	115	17	451	7
	1.5	FRN1.5AQ1□-4E											
	2.2	FRN2.2AQ1□-4E											
	4.0	FRN4.0AQ1□-4E											
	5.5	FRN5.5AQ1□-4E											
	7.5	FRN7.5AQ1□-4E											
	11	FRN11AQ1□-4E											
	15	FRN15AQ1□-4E											
	18.5	FRN18.5AQ1□-4E											
	22	FRN22AQ1□-4E											
	30	FRN30AQ1□-4E											
	37	FRN37AQ1□-4E											
	45	FRN45AQ1□-4E	C	203	585	262	162	100	B	158	22	571	7
	55	FRN55AQ1□-4E											
	75	FRN75AQ1□-4E											
	90	FRN90AQ1□-4E											
	110	FRN110AQ1□-4E											
	132	FRN132AQ1□-4E											
	160	FRN160AQ1□-4E											
	200	FRN200AQ1□-4E											
	220	FRN220AQ1□-4E											
280	FRN280AQ1□-4E												
315	FRN315AQ1□-4E												
355	FRN355AQ1□-4E	D	530	740	315	135	180	D	430	50	710	15	
400	FRN400AQ1□-4E												
500	FRN500AQ1□-4E												
630	FRN630AQ1□-4E												
710	FRN710AQ1□-4E												
880													
1000													
1550													
500													
900													

□ Protective structure: M : IP21, L : IP55, S : IP00. Type of frame: up to 37 kW plastic enclosure and 45 kW and above metal enclosure.

