



E3S-DBP21T

Photoelectric sensor, rectangular shape, red LED, transparent object detection, multi-turn trimmer, 4.5m, PNP, antivalent output, M12 conn.

Specifications

Shape	Cuboid
Sensing method	Retro-reflective
Sensing distance	3500 mm
Sensing distance (min.)	0 mm
Setting method	Manual adjustment
Connection method	Connector M12
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	0.5 ms
Material housing	ABS
Thread size	Other
Product Width (unpacked)	15.8 mm
Product Height (unpacked)	48.5 mm
Product Depth (unpacked)	40.5 mm
Type of light	Polarized red light
Power supply voltage	10-30 V
Features	M.S.R., Transparent detection
Degree of protection (IP)	IP67/IP69K

Accessories



E39-R1S

Accessory photoelectric sensor, reflector, 40 x 60 x 7.5 mm, ABS & Acrylic



E39-R8

Accessory photoelectric sensor, reflector, 100 x100 mm



E39-RP1

Reflector, polarizing, to use with E3ZM-B, 44mm x 64mm



E39-RS1

Reflective tape, self adhesive, 35 x 10 mm



E39-RS2

Accessory photoelectric sensor, reflective tape, 40 x 35 x 0.5 mm, Acrylic, self-adhesive

Related products



M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

CAD Library



E3S-DB Transparent Object Detection Photoelectric Sensor

Brochure

EN

PDF 1.99 MB



E3S-DB Transparent object sensor

Datasheet

EN

PDF 3.98 MB




EAC Mark removal

Discontinuation Notice

EN

PDF 221 KB



PC Monitoring Tool

Software

EN

ZIP 2.36 MB